Application No. 09/751,762 Response dated October 2, 2006 Final Office Action dated May 30, 2006

## LISTING OF THE CLAIMS

The listing of claims will replace all prior versions and listings of claims in the application:

(Previously Presented) A method comprising: 1.

determining if a stalled operation of a first thread is due to a loading of data from a memory device; and

flushing an instruction from said first thread from a pipeline of said processing system if data is to be loaded from said memory device before executing said instruction.

- (Original) The method of claim 1 wherein said memory device is system memory 2. coupled to a memory bus.
- (Original) The method of claim 1 further comprising: 3. marking said instruction as a miss.
- (Original) The method of claim 3 further comprising: 4. rescheduling said instruction to be executed in said pipeline.
- (Previously Presented) A method comprising: 5. determining if a stalled operation of a first thread is due to a loading of data from a memory device; and

Application No. 09/751,762 Response dated October 2, 2006 Final Office Action dated May 30, 2006

flushing an instruction from said first thread from a pipeline of said processing system if data is to be loaded after a predetermined number of clock cycles from said memory device before said instruction can be executed.

KENYON KENYON

- (Original) The method of claim 5 wherein said memory device is system memory 6. coupled to a memory bus.
- (Original) The method of claim 6 further comprising: 7. marking said instruction as a miss.
- (Original) The method of claim 7 further comprising: 8. rescheduling said instruction to be executed in said pipeline.
- (Original) The method of claim 8 further comprising: 9. executing said instruction when data is loaded from said memory device.
- (Previously Presented) A processing system comprising: 10. a scheduler to pass instructions from a first thread and a second thread to an execution pipeline; and

pipeline control logic coupled to said execution pipeline to determine if a stalled execution of said first thread is due to a loading of data from a memory device and to flush an instruction from said first thread from said execution pipeline if data is to be loaded from said memory device before said instruction can be executed.

Atty. Docket No. 2207/10121

Application No. 09/751,762 Response dated October 2, 2006 Final Office Action dated May 30, 2006

- 11. (Original) The processing system of claim 10 wherein said pipeline control logic is to mark said instruction as a miss.
- 12. (Original) The processing system of claim 10 further comprising: an exception and retirement logic coupled to said execution pipeline.
- 13. (Original) The processing system of claim 12 wherein said instruction marked as a miss is to be detected by said exception and retirement logic.
- 14. (Original) The processing system of claim 13 further comprising:a fetch unit to provide said instruction to said scheduler.
- 15. (Previously Presented) The processing system of claim 14 wherein said pipeline control logic is to cause said instruction to be executed if data is loaded from said memory device.
- 16. (Previously Presented) A computing system comprising:
  a memory bus coupled to system memory; and
  a processing system coupled to said memory bus, said processing system including
  - a scheduler to pass instructions from a first thread and a second thread to an execution pipeline; and

pipeline control logic coupled to said execution pipeline to determine if a stalled execution of said first thread is due to a loading of data from system memory and to flush

Application No. 09/751,762 Response dated October 2, 2006 Final Office Action dated May 30, 2006

> an instruction from said first thread from said execution pipeline if data is to be loaded from said system memory before said instruction can be executed.

(Original) The computing system of claim 16 wherein said pipeline control logic is to 17. mark said instruction as a miss.

KENYON KENYON

(Previously Presented) The computing system of claim 16 wherein said processing 18. system further includes

an exception and retirement logic coupled to said execution pipeline.

- (Original) The computing system of claim 18 wherein said instruction marked as a miss 19. is to be detected by said exception and retirement logic.
- (Original) The computing system of claim 19 wherein said processing system further 20. includes
  - a fetch unit to provide said instruction to said scheduler.
- (Original) The computing system of claim 20 wherein said pipeline control logic is to 21. cause said instruction to be executed when data is loaded from said system memory.